

Belgrave EdgeLit Series 1260-72W



Technical Specifications

| ATTRIBUTE | VALUES |
|-------------------------------------|--|
| Wattages | TBC, 52W, 54W, 56W, 58W, 60W, 62W, 64W, 66W, 68W, 70W, 72W |
| Efficacy | 100lm/W, 110lm/W |
| Correlated Colour Index (CRI) | >80, >90, TBC |
| MacAdam Ellipse (SDCM) | <4, <3 |
| IP Rating | 20, TBC |
| IK Rating | 03 |
| Voltage | AC220-240V, 50/60Hz |
| Light Source & Brand | LED: San'an SMD 2835 |
| Driver | Driver: BOKE |
| Size - Length | Length: 1195mmL |
| Size - Width | Width: 595mmW |
| Size - Height | Height: 11mmH |
| Weight | Weight: 5.15kg |
| Beam Angle | TBC, Beam Angle: 90°, Beam Angle: 120° |
| Dimming Options | Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable |
| Material of Housing | Housing Material: Aluminium |
| Material of Optics- Glare control | Optics Material: PMMA |
| Corrosion Resistance | Corrosion Resistance: C4 |
| Operating Temperature | Operating Temperature: -30°C to +40°C |
| Trim / Outer Colour | Trim/Outer: White |
| Reflector / Internal Colour | Reflector/Internal: Opal |
| Correlated Colour Temperature (CCT) | CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 3CCT: 3000K+4000K+5000K |
| Mounting Options | Surface Mounted, TBC, T-Bar Recessed, Plaster Recessed |
| Lens Options | TBC, Frosted PMMA Lens, MicroPrismatic Diffuser |
| Lamp Life | Lamp Life: L80 B10 @ 4K, CRI80 |

Product Options

| ATTRIBUTE | VALUES |
|---------------|-----------------|
| Size - Length | Length: 1195mmL |

| ATTRIBUTE | VALUES |
|-----------------------|--|
| Size - Height | Height: 11mmH |
| Beam Angle | TBC, Beam Angle: 90°, Beam Angle: 120° |
| Dimming Options | Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable |
| Material of Housing | Housing Material: Aluminium |
| Operating Temperature | Operating Temperature: -30°C to +40°C |

Certification and Compliance

