

# Gonn Series - 90

[AES-20-TL-A90]



## Technical Specifications

| ATTRIBUTE                     | VALUES             |
|-------------------------------|--------------------|
| Wattages                      | TBC, 30W, 35W      |
| Efficacy                      | 100lm/W, 110lm/W   |
| Correlated Colour Index (CRI) | >85, >90, >97, TBC |

| ATTRIBUTE                           | VALUES  |
|-------------------------------------|---|
| MacAdam Ellipse (SDCM)              | <3  |
| IP Rating                           | 20, TBC   |
| Voltage                             | AC220-240V  |
| Light Source & Brand                | LED: Bridgelux COB  |
| Driver                              | Driver: Archi   |
| Size - Diameter                     | Diameter: 90mmØ   |
| Size - Height                       | Height: 200mmH  |
| Trim / Outer Colour                 | Trim/Outer: White, Trim/Outer: Black                                    |
| Mounting Options                    | Surface Mounted, TBC, Recessed, Track Mounted                           |
| Beam Angle                          | TBC, Beam Angle: 15°, Beam Angle: 24°, Beam Angle: 38°, Beam Angle: 60° |
| Dimming Options                     | Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable        |
| Correlated Colour Temperature (CCT) | CCT: 2700K, CCT: 3000K, CCT: 3500K, CCT: 4000K, CCT: 5000K              |
| Material of Housing                 | Housing Material: Aluminium   |
| Operating Temperature               | Operating Temperature: -15°C to 40°C                                    |

## Product Options

| ATTRIBUTE             | VALUES  |
|-----------------------|---|
| Size - Diameter       | Diameter: 90mmØ   |
| Size - Height         | Height: 200mmH  |
| Beam Angle            | TBC, Beam Angle: 15°, Beam Angle: 24°, Beam Angle: 38°, Beam Angle: 60° |
| Dimming Options       | Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable        |
| Material of Housing   | Housing Material: Aluminium   |
| Operating Temperature | Operating Temperature: -15°C to 40°C                                    |

## Certification and Compliance

