

Drake Series - 93H

[AES-20-TL-C93H]



Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 30W, 35W, 40W
Efficacy	110lm/W, 120lm/W
Correlated Colour Index (CRI)	>80, >90, >97, TBC

ATTRIBUTE	VALUES
MacAdam Ellipse (SDCM)	<3
IP Rating	20, TBC
Voltage	AC220-240V
Light Source & Brand	LED: Bridgelux COB
Driver	Driver: Archi
Size - Diameter	Diameter: 93mmØ
Size - Height	Height: 135mmH
Trim / Outer Colour	Trim/Outer: White, Trim/Outer: Black
Mounting Options	TBC, Track Mounted
Beam Angle	TBC, Beam Angle: 20°, Beam Angle: 30°, Beam Angle: 45°, Beam Angle: 60°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 2700K, CCT: 3000K, CCT: 3500K, CCT: 4000K, CCT: 5000K
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -15°C to 40°C

Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 93mmØ
Size - Height	Height: 135mmH
Beam Angle	TBC, Beam Angle: 20°, Beam Angle: 30°, Beam Angle: 45°, Beam Angle: 60°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -15°C to 40°C

Certification and Compliance

