

# Amby Series



## Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 20W, 30W, 40W
Efficacy	110lm/W, 120lm/W
Correlated Colour Index (CRI)	>80, >90, TBC
MacAdam Ellipse (SDCM)	<3

ATTRIBUTE	VALUES
IP Rating	20, TBC
Voltage	AC220-240V
Light Source & Brand	LED: Lumileds SMD
Driver	Driver: BOKE
Size - Length	Length: 571mmL
Size - Height	Height: 70mmH
Size - Width	Width: 45mmW
Trim / Outer Colour	Trim/Outer: White, Trim/Outer: Black
Mounting Options	Surface Mounted, TBC, Recessed, Track Mounted
Beam Angle	TBC, Beam Angle: 60° x 90°, Beam Angle: 90° x 90°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 2700K, CCT: 3000K, CCT: 3500K, CCT: 4000K, CCT: 5000K
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -15°C to 40°C

## Product Options

ATTRIBUTE	VALUES
Size - Length	Length: 571mmL
Size - Height	Height: 70mmH
Beam Angle	TBC, Beam Angle: 60° x 90°, Beam Angle: 90° x 90°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -15°C to 40°C

## Certification and Compliance

