

Canterbury Series



Technical Specifications

ATTRIBUTE	VALUES
Wattages	35W, 40W, 50W, 60W, 70W
Efficacy	140lm/W, 150lm/W
Correlated Colour Index (CRI)	CRI: >70, CRI: >80, CRI: >90
MacAdam Ellipse (SDCM)	SDCM: <3

ATTRIBUTE	VALUES
IP Rating	IP20
Voltage	AC220-240V
Light Source & Brand	LED: Philips 2835 SMD, LED: Osram SMD
Driver	Driver: BOKE
Size - Length	Length: 1149mmL
Size - Width	Width: 64mmW
Size - Height	Height: 96mmH
Trim / Outer Colour	Trim/Outer: White, Trim/Outer: Black
Mounting Options	Surface Mounted, Recessed, Track Mounted
Beam Angle	Beam Angle: 30° x 90°, Beam Angle: 60° x 110°, Beam Angle: 90° x 110°, Beam Angle: LR25°, Beam Angle: P18°
Dimming Options	Non-Dimmable, Triac Dimmable, 0-10V Dimmable, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 2700K, CCT: 3000K, CCT: 3500K, CCT: 4000K, CCT: 5000K
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -15°C to 40°C

Product Options

ATTRIBUTE	VALUES
Size - Length	Length: 1149mmL
Size - Height	Height: 96mmH
Beam Angle	Beam Angle: 30° x 90°, Beam Angle: 60° x 110°, Beam Angle: 90° x 110°, Beam Angle: LR25°, Beam Angle: P18°
Dimming Options	Non-Dimmable, Triac Dimmable, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -15°C to 40°C

Certification and Compliance

