


Trida Series - 8850



Technical Specifications

ATTRIBUTE	VALUES
Wattages	8W, 10W, 12W, 14W, 16W, 18W, 20W, 22W, 24W, 26W, 28W, 30W, 32W, 34W, 36W, 38W
Efficacy	80lm/W, 105lm/W
Correlated Colour Index (CRI)	CRI: >80, CRI: >90
MacAdam Ellipse (SDCM)	SDCM: <5, SDCM: <3
IP Rating	IP20, IP40
Voltage	AC85-265V
Operating Temperature	Operating Temperature: -20°C to +45°C
Material of Housing	Housing Material: Aluminium
Light Source & Brand	LED: Lumileds
Driver	Driver: Tridonic
Size - Width	Width: 88mmW
Size - Height	Height: 50mmH
Trim / Outer Colour	Trim/Outer: White, Trim/Outer: Black, Trim/Outer: Silver, Trim/Outer: Custom Colour
Mounting Options	Recessed
Beam Angle	Beam Angle: 120°
Dimming Options	Non-Dimmable, 0-10V Dimmable, DALI Dimmable
Lens Options	Polycarbonate Diffuser, MicroPrismatic Diffuser
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 5000K

Product Options

ATTRIBUTE	VALUES
Operating Temperature	Operating Temperature: -20°C to +45°C
Material of Housing	Housing Material: Aluminium
Size - Height	Height: 50mmH
Beam Angle	Beam Angle: 120°
Dimming Options	Non-Dimmable, 0-10V Dimmable, DALI Dimmable

Certification and Compliance

