

Haden Series - 1500-1800W



Technical Specifications

ATTRIBUTE	VALUES
Wattages	1500W, 1800W
Efficacy	150lm/W
Correlated Colour Index (CRI)	CRI: >70
MacAdam Ellipse (SDCM)	SDCM: <6
IP Rating	IP66
IK Rating	IK09
Voltage	AC100-277V, 50/60Hz
Light Source & Brand	LED: SMD 5050
Driver	Driver: EUM

ATTRIBUTE	VALUES
Size - Length	Length: 934mmL
Size - Width	Width: 678mmW
Size - Height	Height: 545mmH
Weight	Weight: 58kg
Tilt	Tilt: 160°
Beam Angle	Beam Angle: 30°, Beam Angle: 60°, Beam Angle: 90°, Beam Angle: Type II - 117° x 34°
Dimming Options	Non-Dimmable, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Material of Optics	Optics Material: Polycarbonate
Corrosion Resistance	Corrosion Resistance: C5
Operating Temperature	Operating Temperature: -40°C to+50°C
Trim / Outer Colour	Trim/Outer: Black, Trim/Outer: Grey
Reflector / Internal Colour	Reflector/Internal: Black
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 5700K
Mounting Options	Pole Mounted, Wall Mounted
Accessories	ZigBee Controls, 20kV Surge Protection Device, Aiming Position Laser, Anti-glare Cover, Gateway
Lifetime	Reported L80 @ 85° >102,000 Hrs - As outlined within IESNA Standards, Projected Lifetime can be up to 6 x the reported lifetimes

Product Options

ATTRIBUTE	VALUES
Size - Length	Length: 934mmL
Size - Height	Height: 545mmH
Beam Angle	Beam Angle: 30°, Beam Angle: 60°, Beam Angle: 90°, Beam Angle: Type II - 117° x 34°
Dimming Options	Non-Dimmable, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -40°C to+50°C
Accessories	ZigBee Controls, 20kV Surge Protection Device, Aiming Position Laser, Anti-glare Cover, Gateway

Certification and Compliance

