

Padthaway Series - 1200

[AES-25-TR-1200-04]



Technical Specifications

ATTRIBUTE	VALUES
Size - Length	Length: 1200mmL
Wattages	TBC, 20W, 22W, 24W, 26W, 28W, 30W, 32W, 34W, 39W
Efficacy	140lm/W, 160lm/W
Correlated Colour Index (CRI)	>80, TBC
IP Rating	65, TBC
IK Rating	08
MacAdam Ellipse (SDCM)	<5, <3
Voltage	AC220-240V
Light Source & Brand	LED: SMD
Driver	Driver: BOKE

03 8761 6734 sales@ausecotech.com.au <http://ausecotech.com.au> 62 487 717 179

ATTRIBUTE	VALUES
Size - Width	Width: 65mmW
Size - Height	Height: 55mmH
Dimming Options	Non-Dimmable, TBC, 1-10V Dimmable, DALI Dimmable
Mounting Options	Surface Mounted, Suspended, TBC
Beam Angle	TBC, Beam Angle: 120°
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 6000K
Accessories	Microwave Sensor, CCT Selectable Switch, 1.2m Suspension Kit, 2.4m Suspension Kit
Material of Housing	Housing Material: Aluminium
Material of Optics- Glare control	Optics Material: Polycarbonate
Operating Temperature	Operating Temperature: -15°C to 40°C
Weight	Weight: 12.5kg

Product Options

ATTRIBUTE	VALUES
Size - Length	Length: 1200mmL
Size - Height	Height: 55mmH
Dimming Options	Non-Dimmable, TBC, 1-10V Dimmable, DALI Dimmable
Beam Angle	TBC, Beam Angle: 120°
Accessories	Microwave Sensor, CCT Selectable Switch, 1.2m Suspension Kit, 2.4m Suspension Kit
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -15°C to 40°C

Certification and Compliance

