

Padthaway Series - 1200



Technical Specifications

| ATTRIBUTE | VALUES |
|-------------------------------|--|
| Size - Length | Length: 1200mmL |
| Wattages | TBC, 20W, 22W, 24W, 26W, 28W, 30W, 32W, 34W, 39W |
| Efficacy | 140lm/W, 160lm/W |
| Correlated Colour Index (CRI) | >80, TBC |
| IP Rating | 65, TBC |
| IK Rating | 08 |
| MacAdam Ellipse (SDCM) | <5, <3 |
| Voltage | AC220-240V |
| Light Source & Brand | LED: SMD |
| Driver | Driver: BOKE |
| Size - Width | Width: 65mmW |

| ATTRIBUTE | VALUES |
|-------------------------------------|---|
| Size - Height | Height: 55mmH |
| Dimming Options | Non-Dimmable, TBC, 1-10V Dimmable, DALI Dimmable |
| Mounting Options | Surface Mounted, Suspended, TBC |
| Beam Angle | TBC, Beam Angle: 120° |
| Correlated Colour Temperature (CCT) | CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 6000K |
| Accessories | Microwave Sensor, CCT Selectable Switch, 1.2m Suspension Kit, 2.4m Suspension Kit |
| Material of Housing | Housing Material: Aluminium |
| Material of Optics- Glare control | Optics Material: Polycarbonate |
| Operating Temperature | Operating Temperature: -15°C to 40°C |
| Weight | Weight: 12.5kg |

Product Options

| ATTRIBUTE | VALUES |
|-----------------------|---|
| Size - Length | Length: 1200mmL |
| Size - Height | Height: 55mmH |
| Dimming Options | Non-Dimmable, TBC, 1-10V Dimmable, DALI Dimmable |
| Beam Angle | TBC, Beam Angle: 120° |
| Accessories | Microwave Sensor, CCT Selectable Switch, 1.2m Suspension Kit, 2.4m Suspension Kit |
| Material of Housing | Housing Material: Aluminium |
| Operating Temperature | Operating Temperature: -15°C to 40°C |

Certification and Compliance

