

Edith Series - 50 - COB



Technical Specifications

ATTRIBUTE	VALUES
Wattages	3W, 6W
Efficacy	80lm/W
Correlated Colour Index (CRI)	CRI: >80, CRI: >90
MacAdam Ellipse (SDCM)	SDCM: <3
IP Rating	IP66
IK Rating	IK05
Voltage	DC 24V, AC110-240V, 50/60Hz
Light Source & Brand	LED: Cree COB
Driver	Driver: Meanwell, Driver: Done
Size - Length	Length: 50mmL
Size - Width	Width: 50mmW
Size - Height	Height: 100mmH
Weight	Weight: 1kg
Vertical Rotation	Vertical Rotation: 180°
Beam Angle	Beam Angle: 15°, Beam Angle: 24°, Beam Angle: 36°, Beam Angle: 60°
Dimming Options	Non-Dimmable, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Die-Cast ADC12 Aluminum
Material of Optics	Optics Material: 4mm Tempered Glass
Operating Temperature	Operating Temperature: -20°C to +40°C
Trim / Outer Colour	Trim/Outer: White, Trim/Outer: Black, Trim/Outer: Grey
Correlated Colour Temperature (CCT)	CCT: 2700K, CCT: 3000K, CCT: 3500K, CCT: 4000K, CCT: 5000K, CCT: 5700K, CCT: 6500K
Mounting Options	Surface Mounted
Lens Options	Honeycomb Louve
Accessories	Cubic Hood, 25° Cubic Hood
Lamp Life	Lamp Life: L80 B10 @ 4K, CRI80

Product Options

ATTRIBUTE	VALUES
Size - Length	Length: 50mmL

ATTRIBUTE	VALUES
Size - Height	Height: 100mmH
Beam Angle	Beam Angle: 15°, Beam Angle: 24°, Beam Angle: 36°, Beam Angle: 60°
Dimming Options	Non-Dimmable, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Die-Cast ADC12 Aluminum
Operating Temperature	Operating Temperature: -20°C to +40°C
Accessories	Cubic Hood, 25° Cubic Hood

Certification and Compliance

