

Edith Series - 110 - COB

[AES-12-CBD11001]



Technical Specifications

| ATTRIBUTE | VALUES |
|-------------------------------------|---|
| Wattages | TBC, 18W, 24W |
| Efficacy | 80lm/W |
| Correlated Colour Index (CRI) | >80, >90, TBC |
| MacAdam Ellipse (SDCM) | <3 |
| IP Rating | 66, TBC |
| IK Rating | 05 |
| Voltage | AC220-240V, 50/60Hz, DC 24V |
| Light Source & Brand | LED: Cree COB |
| Driver | Driver: Meanwell, Driver: Done |
| Size - Width | Width: 110mmW |
| Size - Height | Height: 194mmH |
| Size - Length | Length: 110mmL |
| Weight | Weight: 2kg |
| Vertical Rotation | Vertical Rotation: 180° |
| Beam Angle | TBC, Beam Angle: 15°, Beam Angle: 24°, Beam Angle: 36°, Beam Angle: 60° |
| Dimming Options | Non-Dimmable, TBC, 0-10V Dimmable, DALI Dimmable |
| Material of Housing | Housing Material: Die-Cast ADC12 Aluminum |
| Material of Optics- Glare control | Optics Material: 4mm Tempered Glass |
| Operating Temperature | Operating Temperature: -20°C to +40°C |
| Trim / Outer Colour | Trim/Outer: White, Trim/Outer: Black, Trim/Outer: Grey |
| Correlated Colour Temperature (CCT) | CCT: 2700K, CCT: 3000K, CCT: 3500K, CCT: 4000K, CCT: 5000K, CCT: 5700K, CCT: 6500K |
| Mounting Options | Surface Mounted, TBC |
| Lens Options | TBC, Honeycomb Louve |
| Accessories | Cubic Hood, 25° Cubic Hood |
| Lifetime | Reported L80 @ 85° >63,500 Hrs - As outlined within IESNA Standards, Projected Lifetime can be up to 6 x the reported lifetimes |

Product Options

| ATTRIBUTE | VALUES |
|-----------------------|---|
| Size - Height | Height: 194mmH |
| Size - Length | Length: 110mmL |
| Beam Angle | TBC, Beam Angle: 15°, Beam Angle: 24°, Beam Angle: 36°, Beam Angle: 60° |
| Dimming Options | Non-Dimmable, TBC, 0-10V Dimmable, DALI Dimmable |
| Material of Housing | Housing Material: Die-Cast ADC12 Aluminum |
| Operating Temperature | Operating Temperature: -20°C to +40°C |
| Accessories | Cubic Hood, 25° Cubic Hood |

Certification and Compliance

