


## Edith Series - 70 - SMD



### Technical Specifications

ATTRIBUTE	VALUES
Wattages	6W, 9W
Efficacy	80lm/W
Correlated Colour Index (CRI)	CRI: >80, CRI: >90
MacAdam Ellipse (SDCM)	SDCM: <3
IP Rating	IP66
IK Rating	IK05
Voltage	AC220-240V, 50/60Hz, DC 24V
Light Source & Brand	LED: CREE SMD
Driver	Driver: Meanwell, Driver: Done
Size - Length	Length: 70mmL
Size - Width	Width: 70mmW
Size - Height	Height: 121mmH
Weight	Weight: 1.5kg
Vertical Rotation	Vertical Rotation: 180°
Beam Angle	Beam Angle: 5°, Beam Angle: 8°, Beam Angle: 10°, Beam Angle: 12°, Beam Angle: 20°, Beam Angle: 25°, Beam Angle: 30°, Beam Angle: 40°, Beam Angle: 60°, Beam Angle: 10° x 22°, Beam Angle: 15° x 55°, Beam Angle: 20° x 60°
Dimming Options	Non-Dimmable, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Die-Cast ADC12 Aluminum
Material of Optics	Optics Material: 4mm Tempered Glass
Operating Temperature	Operating Temperature: -20°C to +40°C
Trim / Outer Colour	Trim/Outer: White, Trim/Outer: Black, Trim/Outer: Grey
Correlated Colour Temperature (CCT)	CCT: 2700K, CCT: 3000K, CCT: 3500K, CCT: 4000K, CCT: 5000K, CCT: 5700K, CCT: 6500K
Mounting Options	Surface Mounted

ATTRIBUTE	VALUES
Lens Options	Honeycomb Louvre
Accessories	Cubic Hood, 25° Cubic Hood
Lamp Life	Lamp Life: L80 B10 @ 4K, CRI80

## Product Options

ATTRIBUTE	VALUES
Size - Length	Length: 70mmL
Size - Height	Height: 121mmH
Beam Angle	Beam Angle: 5°, Beam Angle: 8°, Beam Angle: 10°, Beam Angle: 12°, Beam Angle: 20°, Beam Angle: 25°, Beam Angle: 30°, Beam Angle: 40°, Beam Angle: 60°, Beam Angle: 10° x 22°, Beam Angle: 15° x 55°, Beam Angle: 20° x 60°
Dimming Options	Non-Dimmable, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Die-Cast ADC12 Aluminum
Operating Temperature	Operating Temperature: -20°C to +40°C
Accessories	Cubic Hood, 25° Cubic Hood

## Certification and Compliance

