

Edmonton Series - 466 - SMD

[AES-12-CBD152480]



Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 100W, 120W, 150W
Efficacy	80lm/W
Correlated Colour Index (CRI)	>80, >90, TBC
MacAdam Ellipse (SDCM)	<3
IP Rating	66, TBC
IK Rating	06
Voltage	AC100-305V, 50/60Hz
Driver	Driver: Done
Light Source & Brand	LED: CREE SMD
Size - Length	Length: 466mmL
Size - Width	Width: 90mmW
Size - Height	Height: 212mmH
Weight	Weight: 7.2kg
Vertical Rotation	Vertical Rotation: 180°
Beam Angle	TBC, Beam Angle: 5°, Beam Angle: 8°, Beam Angle: 10°, Beam Angle: 12°, Beam Angle: 20°, Beam Angle: 25°, Beam Angle: 30°, Beam Angle: 40°, Beam Angle: 45°, Beam Angle: 60°, Beam Angle: 10° x 22°, Beam Angle: 15° x 55°, Beam Angle: 20° x 60°
Dimming Options	Non-Dimmable, TBC
Material of Housing	Housing Material: Die-Cast ADC12 Aluminum
Material of Optics- Glare control	Optics Material: 4mm Tempered Glass
Operating Temperature	Operating Temperature: -20°C to +40°C
Trim / Outer Colour	Trim/Outer: White, Trim/Outer: Black, Trim/Outer: Grey
Correlated Colour Temperature (CCT)	CCT: 2700K, CCT: 3000K, CCT: 3500K, CCT: 4000K, CCT: 5000K, CCT: 5700K, CCT: 6500K

ATTRIBUTE	VALUES
Mounting Options	Surface Mounted, TBC
Lens Options	TBC, Honeycomb Louvre
Accessories	Hood
Lifetime	Reported L80 @ 85° >90,700 Hrs - As outlined within IESNA Standards, Projected Lifetime can be up to 6 x the reported lifetimes

Product Options

ATTRIBUTE	VALUES
Size - Length	Length: 466mmL
Size - Height	Height: 212mmH
Beam Angle	TBC, Beam Angle: 5°, Beam Angle: 8°, Beam Angle: 10°, Beam Angle: 12°, Beam Angle: 20°, Beam Angle: 25°, Beam Angle: 30°, Beam Angle: 40°, Beam Angle: 45°, Beam Angle: 60°, Beam Angle: 10° x 22°, Beam Angle: 15° x 55°, Beam Angle: 20° x 60°
Dimming Options	Non-Dimmable, TBC
Material of Housing	Housing Material: Die-Cast ADC12 Aluminum
Operating Temperature	Operating Temperature: -20°C to +40°C
Accessories	Hood

Certification and Compliance

