

Simpson Series - 42 - COB

[AES-12-LM-GD4201-COB]



Technical Specifications

ATTRIBUTE	VALUES
Wattages	3W, 4W, TBC
Efficacy	80lm/W
Correlated Colour Index (CRI)	>80, >90, TBC
MacAdam Ellipse (SDCM)	<3
IP Rating	66, TBC
IK Rating	07
Voltage	DC 24V, AC100-240V, 50/60Hz
Light Source & Brand	LED: Cree COB
Driver	Driver: Without Driver, Driver: KGP
Size - Diameter	Diameter: 42mmØ
Size - Length	Length: 50mmL
Size - Height	Height: 79mmH
Weight	Weight: 0.4kg
Tilt	Tilt: 180°
Beam Angle	TBC, Beam Angle: 15°, Beam Angle: 24°, Beam Angle: 36°, Beam Angle: 60°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Aluminum Alloy
Material of Optics- Glare control	Optics Material: Tempered Glass Diffuser
Operating Temperature	Operating Temperature: -20°C to +40°C
Trim / Outer Colour	Trim/Outer: White, Trim/Outer: Black, Trim/Outer: Dark Grey
Correlated Colour Temperature (CCT)	CCT: 2700K, CCT: 3000K, CCT: 3500K, CCT: 4000K, CCT: 5000K, CCT: 5700K, CCT: 6500K
Mounting Options	Surface Mounted, TBC, Spike Mounted
Lens Options	TBC, Honeycomb Louve
Accessories	Cylindrical Hood, Cylindrical Hood 45°
Lifetime	Reported L80 @ 85° >63,500 Hrs - As outlined within IESNA Standards, Projected Lifetime can be up to 6 x the reported lifetimes

Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 42mmØ
Size - Length	Length: 50mmL
Size - Height	Height: 79mmH
Beam Angle	TBC, Beam Angle: 15°, Beam Angle: 24°, Beam Angle: 36°, Beam Angle: 60°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Aluminum Alloy
Operating Temperature	Operating Temperature: -20°C to +40°C
Accessories	Cylindrical Hood, Cylindrical Hood 45°

Certification and Compliance

