

Ropeley Series



Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 40W, 50W, 60W, 80W, 100W, 120W
Efficacy	100lm/W
Correlated Colour Index (CRI)	>80, >90, TBC
IP Rating	20, TBC
Voltage	AC100-277V
Light Source & Brand	LED: Osram SMD
Driver	Driver: Lifud, Driver: Tridonic, Driver: Meanwell
Size - Diameter	Diameter: 400mmØ, Diameter: 500mmØ, Diameter: 600mmØ, Diameter: 800mmØ, Diameter: 1000mmØ, Diameter: 1200mmØ
Trim / Outer Colour	Trim/Outer: White, Trim/Outer: Black, Trim/Outer: Custom Colour
Mounting Options	TBC, Pendant
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, 1-10V Dimmable, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 6000K
Accessories	Casambi Wireless Controls
Material of Housing	Housing Material: Die-Casting Aluminum
Material of Optics- Glare control	Optics Material: High Transparency PC Diffuser

Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 400mmØ, Diameter: 500mmØ, Diameter: 600mmØ, Diameter: 800mmØ, Diameter: 1000mmØ, Diameter: 1200mmØ
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, 1-10V Dimmable, DALI Dimmable
Accessories	Casambi Wireless Controls
Material of Housing	Housing Material: Die-Casting Aluminum

Certification and Compliance

