

Aberdare Series - 1200



Technical Specifications

ATTRIBUTE	VALUES
Wattages	17W, 34W
Efficacy	120lm/W, 140lm/W, 160lm/W
Correlated Colour Index (CRI)	CRI: >80
MacAdam Ellipse (SDCM)	SDCM: <5
IP Rating	IP40
IK Rating	IK04
Voltage	AC220-240V
Light Source & Brand	LED: SMD
Driver	Driver: BOKE
Size - Length	Length: 1200mmL
Size - Width	Width: 215mmW
Size - Height	Height: 77mmH
Weight	Weight: 17.5kg
Trim / Outer Colour	Trim/Outer: White
Mounting Options	Surface Mounted
Beam Angle	Beam Angle: 120°
Dimming Options	Non-Dimmable, 1-10V Dimmable, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 6000K, CCT: 3CCT: 3000K+4000K+5000K
Accessories	Microwave Sensor
Material of Housing	Housing Material: Frosted Polycarbonate Diffuser
Operating Temperature	Operating Temperature: -15°C to 40°C

Product Options

ATTRIBUTE	VALUES
Size - Length	Length: 1200mmL
Size - Height	Height: 77mmH
Beam Angle	Beam Angle: 120°
Dimming Options	Non-Dimmable, 1-10V Dimmable, DALI Dimmable
Accessories	Microwave Sensor

ATTRIBUTE	VALUES
Material of Housing	Housing Material: Frosted Polycarbonate Diffuser
Operating Temperature	Operating Temperature: -15°C to 40°C

Certification and Compliance

