

# Sky Panel 1230

[AES-08-CSPL30120]



## Technical Specifications

| ATTRIBUTE                           | VALUES   |
|-------------------------------------|--|
| Wattages                            | TBC, 20W, 22W, 24W, 26W, 28W, 30W, 32W, 34W, 36W, 38W, 40W       |
| Efficacy                            | 130lm/W  |
| Correlated Colour Index (CRI)       | >80, >90, TBC  |
| MacAdam Ellipse (SDCM)              | <4, <3   |
| IP Rating                           | 20, TBC  |
| IK Rating                           | 03   |
| Voltage                             | AC220-240V, 50/60Hz  |
| Light Source & Brand                | LED: San'an SMD 2835   |
| Driver                              | Driver: BOKE   |
| Size - Length                       | Length: 1196mmL  |
| Size - Width                        | Width: 296mmW  |
| Size - Height                       | Height: 11mmH  |
| Weight                              | Weight: 2.86kg   |
| Beam Angle                          | TBC, Beam Angle: 90°   |
| Dimming Options                     | Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable |
| Material of Housing                 | Housing Material: Aluminium                                      |
| Material of Optics- Glare control   | Optics Material: Printed Polycarbonate                           |
| Corrosion Resistance                | Corrosion Resistance: C4   |
| Operating Temperature               | Operating Temperature: -20°C to 45°C                             |
| Trim / Outer Colour                 | Trim/Outer: White  |
| Reflector / Internal Colour         | Reflector/Internal: Opal   |
| Correlated Colour Temperature (CCT) | CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 3CCT: 3000K+4000K+5000K |
| Mounting Options                    | Surface Mounted, TBC, T-Bar Recessed, Plaster Recessed           |
| Lens Options                        | TBC, PMMA Diffuser   |
| Lamp Life                           | Lamp Life: L80 B10 @ 4K, CRI80                                   |

## Product Options

| ATTRIBUTE     | VALUES          |
|---------------|-----------------|
| Size - Length | Length: 1196mmL |

| ATTRIBUTE             | VALUES   |
|-----------------------|--|
| Size - Height         | Height: 11mmH  |
| Beam Angle            | TBC, Beam Angle: 90°   |
| Dimming Options       | Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable |
| Material of Housing   | Housing Material: Aluminium                                      |
| Operating Temperature | Operating Temperature: -20°C to 45°C                             |

## Certification and Compliance

