

Switch Series - 6W-B



Technical Specifications

ATTRIBUTE	VALUES
Wattages	2, 4, 6, TBC
Efficacy	122lm/W
Correlated Colour Index (CRI)	>80, >97, TBC
IP Rating	20, 44, 65, TBC
Voltage	AC220-240V
Trim / Outer Colour	Trim/Outer: White, Trim/Outer: Black
Driver	Driver: Lifud
Size - Diameter	Diameter: 35mmØ

ATTRIBUTE	VALUES
Size - Height	Height: 42mmH
Mounting Options	TBC, Recessed
Beam Angle	TBC, Beam Angle: 20°, Beam Angle: 26°, Beam Angle: 38°, Beam Angle: 46°, Beam Angle: 60°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 2700K, CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 5500K, CCT: 6000K, CCT: 6700K
Accessories	Honeycomb Optics, Frosted Centre
Material of Housing	Housing Material: Die-Casting Aluminum
Operating Temperature	Operating Temperature: -20°C to +50°C
Light Source & Brand	LED: Citizen COB
Lifetime	Reported L80 @ 55° >55,000 Hrs - As outlined within IESNA Standards, Projected Lifetime can be up to 6 x the reported lifetimes

Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 35mmØ
Size - Height	Height: 42mmH
Beam Angle	TBC, Beam Angle: 20°, Beam Angle: 26°, Beam Angle: 38°, Beam Angle: 46°, Beam Angle: 60°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Accessories	Honeycomb Optics, Frosted Centre
Material of Housing	Housing Material: Die-Casting Aluminum
Operating Temperature	Operating Temperature: -20°C to +50°C

Certification and Compliance

