

# Fisher Series - 1200

## Technical Specifications

ATTRIBUTE	VALUES
Wattages	35W
Efficacy	120lm/W, 140lm/W, 160lm/W
Correlated Colour Index (CRI)	CRI: >80
MacAdam Ellipse (SDCM)	SDCM: <5
IP Rating	IP20
IK Rating	IK07
Voltage	AC220-240V
Light Source & Brand	LED: SMD
Driver	Driver: Eaglerise
Size - Length	Length: 1200mmL
Size - Width	Width: 200mmW
Size - Height	Height: 55mmH
Trim / Outer Colour	Trim/Outer: White
Mounting Options	Surface Mounted, Suspended
Beam Angle	Beam Angle: 80°
Dimming Options	Non-Dimmable, 1-10V Dimmable, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 6000K
Accessories	Microwave Sensor, CCT Selectable Switch
Material of Housing	Housing Material: Polycarbonate
Material of Optics	Optics Material: PC Cover & Diffuser
Operating Temperature	Operating Temperature: -10°C to +40°C

## Product Options

ATTRIBUTE	VALUES
Size - Length	Length: 1200mmL

ATTRIBUTE	VALUES
Size - Height	Height: 55mmH
Beam Angle	Beam Angle: 80°
Dimming Options	Non-Dimmable, 1-10V Dimmable, DALI Dimmable
Accessories	Microwave Sensor, CCT Selectable Switch
Material of Housing	Housing Material: Polycarbonate
Operating Temperature	Operating Temperature: -10°C to +40°C

## Certification and Compliance

