

# Banca Series - 1500 x 6068

[AES-04-CC6068-1500]



## Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 94W
Efficacy	80lm/W
Correlated Colour Index (CRI)	>80, >90, TBC
MacAdam Ellipse (SDCM)	<3
IP Rating	20, TBC
Voltage	AC220-240V
Operating Temperature	Operating Temperature: -20°C to +45°C
Material of Housing	Housing Material: Aluminium
Light Source & Brand	LED: Osram SMD
Driver	Driver: Lifud
Size - Diameter	Diameter: 1500mmØ
Size - Width	Width: 60mmW
Size - Height	Height: 68mmH
Trim / Outer Colour	Trim/Outer: White, Trim/Outer: Black, Trim/Outer: Silver, Trim/Outer: Custom Colour
Mounting Options	Surface Mounted, TBC, Suspended 2m, Suspended 5m, Rod Suspended
Beam Angle	TBC, Beam Angle: 120°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Lens Options	Polycarbonate Diffuser, TBC
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 6000K

## Product Options

ATTRIBUTE	VALUES
Operating Temperature	Operating Temperature: -20°C to +45°C
Material of Housing	Housing Material: Aluminium
Size - Diameter	Diameter: 1500mmØ
Size - Height	Height: 68mmH
Beam Angle	TBC, Beam Angle: 120°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable

## Certification and Compliance

