

Harvey Series - 100-150W



Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 100W, 150W
Efficacy	140lm/W, 190lm/W
Correlated Colour Index (CRI)	>80, TBC
MacAdam Ellipse (SDCM)	<6
IP Rating	65, TBC
IK Rating	10
Voltage	AC120-277V, 50/60Hz
Light Source & Brand	LED: Lumileds 2835
Driver	Driver: SOSEN
Size - Diameter	Diameter: 255mmØ
Size - Height	Height: 152mmH
Weight	Weight: 1.8kg
Beam Angle	TBC, Beam Angle: 60°, Beam Angle: 90°, Beam Angle: 120°
Dimming Options	Non-Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Die-Casting Aluminum
Material of Optics- Glare control	Optics Material: Polycarbonate
Corrosion Resistance	Corrosion Resistance: C5
Operating Temperature	Operating Temperature: -40°C to+50°C
Trim / Outer Colour	Trim/Outer: Black
Reflector / Internal Colour	Reflector/Internal: White
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 5700K, CCT: 6500K
Mounting Options	Suspended, TBC, Wall Mounted, Ceiling Mounted
Accessories	Microwave Sensor, PIR Sensor, IP65 Connectors, Aluminium Reflector, PC Reflector, Remote Control, Chain
Lifetime	Reported L80 @ 85° >102,000 Hrs - As outlined within IESNA Standards, Projected Lifetime can be up to 6 x the reported lifetimes

Product Options

ATTRIBUTE	VALUES
-----------	--------

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 255mmØ
Size - Height	Height: 152mmH
Beam Angle	TBC, Beam Angle: 60°, Beam Angle: 90°, Beam Angle: 120°
Dimming Options	Non-Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Die-Casting Aluminum
Operating Temperature	Operating Temperature: -40°C to+50°C
Accessories	Microwave Sensor, PIR Sensor, IP65 Connectors, Aluminium Reflector, PC Reflector, Remote Control, Chain

Certification and Compliance

