

Beacon Series Frameless- 496

[AES-12-LIGL452436-496]



Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 24W, 36W, 48W, 72W
Efficacy	90lm/W, 100lm/W
Correlated Colour Index (CRI)	>80, >90, TBC
MacAdam Ellipse (SDCM)	<5, <3
IP Rating	67, TBC

03 8761 6734 sales@ausecotech.com.au <http://ausecotech.com.au> 62 487 717 179

ATTRIBUTE	VALUES
IK Rating	09
Voltage	AC220-240V
Light Source & Brand	LED: Osram SMD, LED: CREE SMD
Size - Length	Length: 496mmL
Size - Width	Width: 45mmW
Size - Height	Height: 80mmH
Mounting Options	TBC, Recessed
Beam Angle	TBC, Beam Angle: 10°, Beam Angle: 25°, Beam Angle: 45°, Beam Angle: 60°, Beam Angle: 100°, Beam Angle: 10° x 60°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 2700K, CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 6000K, CCT: 6500K, CCT: RGB, CCT: RGBW
Accessories	DMX Controls
Lens Options	TBC, PMMA + Anti-UV Lens
Material of Housing	Housing Material: Stainless Steel
Operating Temperature	Operating Temperature: -20°C to +40°C
Lifetime	Reported L80 @ 85° >90,700 Hrs - As outlined within IESNA Standards, Projected Lifetime can be up to 6 x the reported lifetimes

Product Options

ATTRIBUTE	VALUES
Size - Length	Length: 496mmL
Size - Height	Height: 80mmH
Beam Angle	TBC, Beam Angle: 10°, Beam Angle: 25°, Beam Angle: 45°, Beam Angle: 60°, Beam Angle: 100°, Beam Angle: 10° x 60°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Accessories	DMX Controls
Material of Housing	Housing Material: Stainless Steel
Operating Temperature	Operating Temperature: -20°C to +40°C

Certification and Compliance

