

Fleming Series - 70

[AES-15-LS3001-R65]





Technical Specifications

ATTRIBUTE	VALUES
Wattages	6W, 8W, 10W, 12W, TBC
Efficacy	90lm/W
Correlated Colour Index (CRI)	>90, >95, >97, TBC
Voltage	AC220-240V
Light Source & Brand	LED: Bridgelux COB
Size - Diameter	Diameter: 73mmØ
Size - Height	Height: 118mmH
Cut Out Size - Diameter	Cut Out: 67mmØ
Trim / Outer Colour	Trim/Outer: White, Trim/Outer: Black
Mounting Options	Surface Mounted, TBC
Beam Angle	TBC, Beam Angle: 12°, Beam Angle: 24°, Beam Angle: 38°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 2700K, CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 5700K, CCT: 6000K, CCT: 6500K
Material of Housing	Housing Material: Die Cast Aluminium
Operating Temperature	Operating Temperature: -20°C to +40°C

Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 73mmØ
Size - Height	Height: 118mmH
Beam Angle	TBC, Beam Angle: 12°, Beam Angle: 24°, Beam Angle: 38°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Die Cast Aluminium
Operating Temperature	Operating Temperature: -20°C to +40°C

Certification and Compliance

