

Alpine Series - 60



Technical Specifications

ATTRIBUTE	VALUES
Wattages	6W, 8W, 10W, 12W
Efficacy	90lm/W
Correlated Colour Index (CRI)	CRI: >90, CRI: >95, CRI: >97
Voltage	AC220-240V
Light Source & Brand	LED: Bridgelux COB, LED: Cree COB
Size - Diameter	Diameter: 60mmØ
Size - Height	Height: 160mmH

03 8761 6734 accounts@ausecotech.com.au <http://ausecotech.com.au> 62 487 717 179

ATTRIBUTE	VALUES
Trim / Outer Colour	Trim/Outer: White, Trim/Outer: Black
Mounting Options	Surface Mounted
Beam Angle	Beam Angle: 12°, Beam Angle: 24°, Beam Angle: 38°
Dimming Options	Non-Dimmable, Triac Dimmable, 0-10V Dimmable, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 2700K, CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 5700K, CCT: 6000K, CCT: 6500K
Material of Housing	Housing Material: Die Cast Aluminium
Operating Temperature	Operating Temperature: -20°C to +40°C

Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 60mmØ
Size - Height	Height: 160mmH
Beam Angle	Beam Angle: 12°, Beam Angle: 24°, Beam Angle: 38°
Dimming Options	Non-Dimmable, Triac Dimmable, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Die Cast Aluminium
Operating Temperature	Operating Temperature: -20°C to +40°C

Certification and Compliance

