

Raglan Series



Technical Specifications

ATTRIBUTE	VALUES
Wattages	50W, 100W, 150W, 200W, 240W, 300W
Efficacy	150lm/W
Correlated Colour Index (CRI)	CRI: >70, CRI: >80
IP Rating	IP66
IK Rating	IK08
Voltage	AC220-240V

ATTRIBUTE	VALUES
Size - Length	Length: 276mmL, Length: 322mmL, Length: 357mmL, Length: 391mmL, Length: 440mmL
Size - Width	Width: 246mmW, Width: 286mmW, Width: 310mmW, Width: 353mmW, Width: 419mmW
Size - Height	Height: 66mmH, Height: 73mmH, Height: 75mmH, Height: 79mmH, Height: 87mmH
Weight	Weight: 2.1kg, Weight: 3.1kg, Weight: 3.7kg, Weight: 5kg, Weight: 6.6kg, Weight: 6.8kg
Mounting Options	Pole Mounted, Bracket Mounted
Beam Angle	Beam Angle: 25°, Beam Angle: 60°, Beam Angle: Type I - 26° x 60°, Beam Angle: Type III - 55° x 125°
Dimming Options	Non-Dimmable, Triac Dimmable, 0-10V Dimmable
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 5000K

Product Options

ATTRIBUTE	VALUES
Size - Length	Length: 276mmL, Length: 322mmL, Length: 357mmL, Length: 391mmL, Length: 440mmL
Size - Height	Height: 66mmH, Height: 73mmH, Height: 75mmH, Height: 79mmH, Height: 87mmH
Beam Angle	Beam Angle: 25°, Beam Angle: 60°, Beam Angle: Type I - 26° x 60°, Beam Angle: Type III - 55° x 125°
Dimming Options	Non-Dimmable, Triac Dimmable, 0-10V Dimmable

Certification and Compliance

