

Abbeywood Series - 50W

[AES-01-FL44-50W]



Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 50W
Efficacy	150lm/W
Correlated Colour Index (CRI)	>70, >80, TBC
MacAdam Ellipse (SDCM)	<5
IP Rating	66, TBC
IK Rating	08
Voltage	AC220-240V, 50/60Hz
Light Source & Brand	LED: SMD
Driver	Driver: Done
Size - Length	Length: 292mmL
Size - Width	Width: 245mmW
Size - Height	Height: 55mmH
Weight	Weight: 2.4kg
Vertical Rotation	Vertical Rotation: 45°
Beam Angle	TBC, Beam Angle: F06401 - 55°x 125°, tilt 55°, Beam Angle: F06403 - 26°x 60°, tilt 10°, Beam Angle: F06404 - 25°, Beam Angle: F06402 - 60°
Dimming Options	Non-Dimmable, TBC, 0-10V Dimmable
Material of Housing	Housing Material: Die-Casting Aluminum Alloy
Material of Optics-Glare control	Optics Material: Polycarbonate
Corrosion Resistance	Corrosion Resistance: C3
Operating Temperature	Operating Temperature: -30°C to +50°C
Trim / Outer Colour	Trim/Outer: Black
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 5000K
Mounting Options	TBC, Pole Mounted, Bracket Mounted
Accessories	42mm Pole Mounting Adaptor, 76mm Pole Mounting Adaptor, 60mm Pole Mounting Adaptor, Outrigger Arm, Clamp Bracket (40mm-90mm pole)
Lamp Life	Lamp Life: L80 B10 @ 4K, CRI80

Product Options

ATTRIBUTE	VALUES
Size - Length	Length: 292mmL
Size - Height	Height: 55mmH
Beam Angle	TBC, Beam Angle: F06401 - 55°x 125°, tilt 55°, Beam Angle: F06403 - 26°x 60°, tilt 10°, Beam Angle: F06404 - 25°, Beam Angle: F06402 - 60°
Dimming Options	Non-Dimmable, TBC, 0-10V Dimmable
Material of Housing	Housing Material: Die-Casting Aluminum Alloy
Operating Temperature	Operating Temperature: -30°C to +50°C
Accessories	42mm Pole Mounting Adaptor, 76mm Pole Mounting Adaptor, 60mm Pole Mounting Adaptor, Outrigger Arm, Clamp Bracket (40mm-90mm pole)

Certification and Compliance

