

Mimosa Series R - 15W

[AES-15-3001K]



Technical Specifications

ATTRIBUTE	VALUES
Wattages	11W, 13W, TBC, 15W
Efficacy	90lm/W
Correlated Colour Index (CRI)	>90, >95, >97, TBC
Voltage	AC220-240V
Light Source & Brand	LED: Bridgelux COB

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 90mmØ
Size - Height	Height: 90mmH
Trim / Outer Colour	Trim/Outer: White, Trim/Outer: Black
Mounting Options	Surface Mounted, TBC
Beam Angle	TBC, Beam Angle: 20°, Beam Angle: 40°, Beam Angle: 60°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 2700K, CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 5700K, CCT: 6000K, CCT: 6500K
Material of Housing	Housing Material: Die Cast Aluminium
Operating Temperature	Operating Temperature: -20°C to +40°C

Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 90mmØ
Size - Height	Height: 90mmH
Beam Angle	TBC, Beam Angle: 20°, Beam Angle: 40°, Beam Angle: 60°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Die Cast Aluminium
Operating Temperature	Operating Temperature: -20°C to +40°C

Certification and Compliance

