

## Mimosa Series R - 30W



### Technical Specifications

| ATTRIBUTE                     | VALUES             |
|-------------------------------|--------------------|
| Wattages                      | TBC, 26W, 28W, 30W |
| Efficacy                      | 90lm/W             |
| Correlated Colour Index (CRI) | >90, >95, >97, TBC |
| Voltage                       | AC220-240V         |
| Light Source & Brand          | LED: Bridgelux COB |
| Size - Diameter               | Diameter: 130mmØ   |
| Size - Height                 | Height: 130mmH     |

03 8761 6734 sales@ausecotech.com.au <http://ausecotech.com.au> 62 487 717 179

| ATTRIBUTE                           | VALUES   |
|-------------------------------------|--|
| Trim / Outer Colour                 | Trim/Outer: White, Trim/Outer: Black   |
| Mounting Options                    | Surface Mounted, TBC   |
| Beam Angle                          | TBC, Beam Angle: 20°, Beam Angle: 40°, Beam Angle: 60°                             |
| Dimming Options                     | Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable                   |
| Correlated Colour Temperature (CCT) | CCT: 2700K, CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 5700K, CCT: 6000K, CCT: 6500K |
| Material of Housing                 | Housing Material: Die Cast Aluminium   |
| Operating Temperature               | Operating Temperature: -20°C to +40°C  |

## Product Options

| ATTRIBUTE             | VALUES   |
|-----------------------|--|
| Size - Diameter       | Diameter: 130mmØ   |
| Size - Height         | Height: 130mmH   |
| Beam Angle            | TBC, Beam Angle: 20°, Beam Angle: 40°, Beam Angle: 60°           |
| Dimming Options       | Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable |
| Material of Housing   | Housing Material: Die Cast Aluminium                             |
| Operating Temperature | Operating Temperature: -20°C to +40°C                            |

## Certification and Compliance

