

# Mimosa Series R - 50W



## Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 40W, 42W, 44W, 46W, 48W, 50W
Efficacy	90lm/W
Correlated Colour Index (CRI)	>90, >95, >97, TBC
Voltage	AC220-240V
Light Source & Brand	LED: Bridgelux COB
Size - Diameter	Diameter: 195mmØ

ATTRIBUTE	VALUES
Size - Height	Height: 190mmH
Trim / Outer Colour	Trim/Outer: White, Trim/Outer: Black
Mounting Options	Surface Mounted, TBC
Beam Angle	TBC, Beam Angle: 20°, Beam Angle: 40°, Beam Angle: 60°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 2700K, CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 5700K, CCT: 6000K, CCT: 6500K
Material of Housing	Housing Material: Die Cast Aluminium
Operating Temperature	Operating Temperature: -20°C to +40°C

## Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 195mmØ
Size - Height	Height: 190mmH
Beam Angle	TBC, Beam Angle: 20°, Beam Angle: 40°, Beam Angle: 60°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Die Cast Aluminium
Operating Temperature	Operating Temperature: -20°C to +40°C

## Certification and Compliance

