

# Yaamba Series



## Technical Specifications

ATTRIBUTE	VALUES
Wattages	50W, 100W, 150W, 200W, 240W, 300W
Efficacy	150lm/W
Correlated Colour Index (CRI)	CRI: >70
IP Rating	IP66
IK Rating	IK08
Voltage	AC100-277V

ATTRIBUTE	VALUES
Size - Length	Length: 362mmL, Length: 391mmL, Length: 420mmL, Length: 456mmL, Length: 516mmL
Size - Width	Width: 256mmW, Width: 297mmW, Width: 327mmW, Width: 370mmW, Width: 433mmW
Size - Height	Height: 66mmH, Height: 68mmH, Height: 74mmH, Height: 75mmH
Weight	Weight: 3.7kg, Weight: 4.5kg, Weight: 5.4kg, Weight: 6.7kg, Weight: 9.2kg
Mounting Options	Wall Mounted
Beam Angle	Beam Angle: 25°, Beam Angle: 60°, Beam Angle: Type I - 26° x 60°, Beam Angle: Type III - 55° x 125°
Dimming Options	Non-Dimmable, 0-10V Dimmable, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 5000K

## Product Options

ATTRIBUTE	VALUES
Size - Length	Length: 362mmL, Length: 391mmL, Length: 420mmL, Length: 456mmL, Length: 516mmL
Size - Height	Height: 66mmH, Height: 68mmH, Height: 74mmH, Height: 75mmH
Beam Angle	Beam Angle: 25°, Beam Angle: 60°, Beam Angle: Type I - 26° x 60°, Beam Angle: Type III - 55° x 125°
Dimming Options	Non-Dimmable, 0-10V Dimmable, DALI Dimmable

## Certification and Compliance

