

Yaamba Series

[AES-01-FL57]



Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 50W, 100W, 150W, 200W, 240W, 300W
Efficacy	150lm/W
Correlated Colour Index (CRI)	>70, TBC
IP Rating	66, TBC
IK Rating	08

03 8761 6734 sales@ausecotech.com.au <http://ausecotech.com.au> 62 487 717 179

ATTRIBUTE	VALUES
Voltage	AC100-277V
Size - Length	Length: 362mmL, Length: 391mmL, Length: 420mmL, Length: 456mmL, Length: 516mmL
Size - Width	Width: 256mmW, Width: 297mmW, Width: 327mmW, Width: 370mmW, Width: 433mmW
Size - Height	Height: 66mmH, Height: 68mmH, Height: 74mmH, Height: 75mmH
Weight	Weight: 3.7kg, Weight: 4.5kg, Weight: 5.4kg, Weight: 6.7kg, Weight: 9.2kg
Mounting Options	TBC, Wall Mounted
Beam Angle	TBC, Beam Angle: 25°, Beam Angle: 60°, Beam Angle: Type I - 26° x 60°, Beam Angle: Type III - 55° x 125°
Dimming Options	Non-Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 5000K

Product Options

ATTRIBUTE	VALUES
Size - Length	Length: 362mmL, Length: 391mmL, Length: 420mmL, Length: 456mmL, Length: 516mmL
Size - Height	Height: 66mmH, Height: 68mmH, Height: 74mmH, Height: 75mmH
Beam Angle	TBC, Beam Angle: 25°, Beam Angle: 60°, Beam Angle: Type I - 26° x 60°, Beam Angle: Type III - 55° x 125°
Dimming Options	Non-Dimmable, TBC, 0-10V Dimmable, DALI Dimmable

Certification and Compliance

