

Tomakin Series

[AES-12-HLM2003]



Technical Specifications

ATTRIBUTE	VALUES
Wattages	1.2W, 1.5W, TBC
Efficacy	80lm/W

ATTRIBUTE	VALUES
Correlated Colour Index (CRI)	>80, >85, >90, TBC
IP Rating	67, TBC
IK Rating	09
Voltage	AC85-265V
Light Source & Brand	LED: Cree COB
Size - Diameter	Diameter: 20mmØ
Size - Height	Height: 30mmH
Trim / Outer Colour	Trim/Outer: Grey
Mounting Options	TBC, Recessed
Beam Angle	TBC, Beam Angle: Symmetric 30°/55°, Beam Angle: Asymmetric 55°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 2700K, CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 6000K, CCT: 6500K, CCT: RGB
Material of Housing	Housing Material: Stainless Steel and Aluminum
Operating Temperature	Operating Temperature: -20°C to +45°C
Lifetime	Reported L80 @ 85° >63,500 Hrs - As outlined within IESNA Standards, Projected Lifetime can be up to 6 x the reported lifetimes

Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 20mmØ
Size - Height	Height: 30mmH
Beam Angle	TBC, Beam Angle: Symmetric 30°/55°, Beam Angle: Asymmetric 55°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Stainless Steel and Aluminum
Operating Temperature	Operating Temperature: -20°C to +45°C

Certification and Compliance

