

Paddington Series - 50W

[AES-01-FL23-50W]



Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 50W
Efficacy	150lm/W
Correlated Colour Index (CRI)	>70, >80, TBC
IP Rating	66, TBC

ATTRIBUTE	VALUES
IK Rating	08
Voltage	AC220-240V, 50/60Hz
Light Source & Brand	LED: SMD 2835
Driver	Driver: Done
Size - Length	Length: 267mmL
Size - Width	Width: 228mmW
Size - Height	Height: 55mmH
Weight	Weight: 1.8kg
Beam Angle	TBC, F06401, F06402, F06403, F06404, F00A23
Dimming Options	Non-Dimmable, TBC, 0-10V Dimmable
Corrosion Resistance	Corrosion Resistance: C3
Trim / Outer Colour	Trim/Outer: Black
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 5000K
Mounting Options	TBC, Pole Mounted, Bracket Mounted
Accessories	42mm Pole Mounting Adaptor, 76mm Pole Mounting Adaptor, 60mm Pole Mounting Adaptor, Outrigger Arm, Clamp Bracket (40mm-90mm pole)
Lifetime	Reported L80 @ 85° >60,000 Hrs - As outlined within IESNA Standards, Projected Lifetime can be up to 6 x the reported lifetimes

Product Options

ATTRIBUTE	VALUES
Size - Length	Length: 267mmL
Size - Height	Height: 55mmH
Beam Angle	TBC, F06401, F06402, F06403, F06404, F00A23
Dimming Options	Non-Dimmable, TBC, 0-10V Dimmable
Accessories	42mm Pole Mounting Adaptor, 76mm Pole Mounting Adaptor, 60mm Pole Mounting Adaptor, Outrigger Arm, Clamp Bracket (40mm-90mm pole)

Certification and Compliance

