

Werona Series - Down

[AES-27-WL85-8]



Technical Specifications

ATTRIBUTE	VALUES
Wattages	4W, 6W, 8W, TBC, 15W
Efficacy	90lm/W
Correlated Colour Index (CRI)	>80, TBC
MacAdam Ellipse (SDCM)	<6

ATTRIBUTE	VALUES
IP Rating	65, TBC
IK Rating	06
Voltage	AC220-240V
Light Source & Brand	LED: SMD
Driver	Driver: Built In
Size - Diameter	Diameter: 70mmØ
Size - Height	Height: 143mmH
Trim / Outer Colour	Trim/Outer: White, Trim/Outer: Black
Mounting Options	TBC, Wall Mounted
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Beam Angle	TBC, Beam Angle: 45°
Correlated Colour Temperature (CCT)	CCT: 2700K, CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 5700K, CCT: 3CCT: 3000K+4000K+5700K
Material of Optics- Glare control	Optics Material: Polycarbonate
Material of Housing	Housing Material: Die-Casting Aluminum
Operating Temperature	Operating Temperature: -15°C to 40°C

Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 70mmØ
Size - Height	Height: 143mmH
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Beam Angle	TBC, Beam Angle: 45°
Material of Housing	Housing Material: Die-Casting Aluminum
Operating Temperature	Operating Temperature: -15°C to 40°C

Certification and Compliance

