Australian EcoTech Solutions
1/123 Merrindale Drive
Croydon South VIC 3136
Australia

Werona Series - Up/Down

[AES-27-WL85-15]



Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 2 x 3.5W (7W), 2 x 5.5W (11W), 7.5W*2 - REPLACE
Efficacy	90lm/W
Correlated Colour Index (CRI)	>80, TBC
MacAdam Ellipse (SDCM)	<6
IP Rating	65, TBC

Australian EcoTech Solutions
1/123 Merrindale Drive
Croydon South VIC 3136
Australia

ATTRIBUTE	VALUES
IK Rating	06
Voltage	AC220-240V
Light Source & Brand	LED: SMD
Driver	Driver: Built In
Size - Diameter	Diameter: 70mmØ
Size - Height	Height: 179mmH
Trim / Outer Colour	TBC, Corten, Trim/Outer: Powder Coat Grey, Trim/Outer: White, Trim/Outer: Black
Mounting Options	TBC, Wall Mounted
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Beam Angle	TBC, Beam Angle: 45°
Correlated Colour Temperature (CCT)	CCT: 2700K, CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 5700K, CCT: 3CCT: 3000K+4000K+5700K
Material of Optics- Glare control	Optics Material: Polycarbonate
Material of Housing	Housing Material: Die-Casting Aluminum
Operating Temperature	Operating Temperature: -15°C to 40°C

Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 70mmØ
Size - Height	Height: 179mmH
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Beam Angle	TBC, Beam Angle: 45°
Material of Housing	Housing Material: Die-Casting Aluminum
Operating Temperature	Operating Temperature: -15°C to 40°C

Certification and Compliance





