

# Fairdale Series



## Technical Specifications

ATTRIBUTE	VALUES
Wattages	35W, 100W, 150W
Efficacy	70lm/W, 100lm/W
Correlated Colour Index (CRI)	CRI: >70, CRI: >80, CRI: >90
IP Rating	IP66
IK Rating	IK08

ATTRIBUTE	VALUES
Voltage	AC100-277V
Light Source & Brand	LED: CREE
Size - Length	Length: 220mmL, Length: 450mmL
Size - Width	Width: 330mmW, Width: 452mmW
Size - Height	Height: 70mmH, Height: 100mmH, Height: 160mmH
Mounting Options	Spike Mounted, Bracket Mounted
Beam Angle	Beam Angle: 3°, Beam Angle: 8°, Beam Angle: 12°, Beam Angle: 30°, Beam Angle: 60°, Beam Angle: 75°, Beam Angle: 15° x 30°, Beam Angle: 20° x 60°
Dimming Options	Non-Dimmable, 0-10V Dimmable, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 2200K, CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: RGB, CCT: RGBW, CCT: Tunable White
Accessories	Casambi Wireless Controls, DMX Controls, Bluetooth

## Product Options

ATTRIBUTE	VALUES
Size - Length	Length: 220mmL, Length: 450mmL
Size - Height	Height: 70mmH, Height: 100mmH, Height: 160mmH
Beam Angle	Beam Angle: 3°, Beam Angle: 8°, Beam Angle: 12°, Beam Angle: 30°, Beam Angle: 60°, Beam Angle: 75°, Beam Angle: 15° x 30°, Beam Angle: 20° x 60°
Dimming Options	Non-Dimmable, 0-10V Dimmable, DALI Dimmable
Accessories	Casambi Wireless Controls, DMX Controls, Bluetooth

## Certification and Compliance

