

Paget Series - 198



Technical Specifications

ATTRIBUTE	VALUES
Wattages	30W, 32W, 34W, 36W, 38W, 40W
Efficacy	80-90lm/W
Correlated Colour Index (CRI)	CRI: >80, CRI: >90
MacAdam Ellipse (SDCM)	SDCM: <3
IP Rating	IP20
Voltage	AC220-240V, 50/60Hz
Light Source & Brand	LED: Citizen COB
Driver	Driver: AIDimming, Driver: Boke Flicker Free
Size - Diameter	Diameter: 198mmØ
Size - Height	Height: 210mmH
Cut Out Size - Diameter	Cut Out: 185mmØ
Weight	Weight: 1.57kg
Tilt	Tilt: 15°-20°
Beam Angle	Beam Angle: 15°, Beam Angle: 24°, Beam Angle: 38°, Beam Angle: 55°
Dimming Options	Non-Dimmable, Triac Dimmable, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Material of Optics	Optics Material: Aluminium
Operating Temperature	Operating Temperature: -15°C to 40°C
Trim / Outer Colour	Trim/Outer: White
Reflector / Internal Colour	Reflector/Internal: Shiny Silver, Reflector/Internal: Matt Silver
Correlated Colour Temperature (CCT)	CCT: 2700K, CCT: 3000K, CCT: 3500K, CCT: 4000K, CCT: 5000K
Mounting Options	Recessed
Lens Options	Reflector
Lamp Life	Lamp Life: L80 B10 @ 4K, CRI80

Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 198mmØ
Size - Height	Height: 210mmH
Beam Angle	Beam Angle: 15°, Beam Angle: 24°, Beam Angle: 38°, Beam Angle: 55°

ATTRIBUTE	VALUES
Dimming Options	Non-Dimmable, Triac Dimmable, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -15°C to 40°C

Certification and Compliance

