

# Jacka Series

[AES-01-HB37]



## Technical Specifications

| ATTRIBUTE                     | VALUES  |
|-------------------------------|---|
| Wattages                      | TBC, 430W, 432W, 434W, 436W, 438W, 440W, 442W, 444W, 446W, 448W, 450W |
| Efficacy                      | 140lm/W, 160lm/W  |
| Correlated Colour Index (CRI) | >70, >80, TBC   |
| IP Rating                     | 66, TBC   |
| IK Rating                     | 08  |

03 8761 6734 sales@ausecotech.com.au <http://ausecotech.com.au> 62 487 717 179

| ATTRIBUTE                           | VALUES  |
|-------------------------------------|---|
| Voltage                             | AC100-277V, AC277-480V  |
| Mounting Options                    | Suspended, TBC, Bracket Mounted   |
| Beam Angle                          | TBC, Beam Angle: 15°, Beam Angle: 30°, Beam Angle: 60°, Beam Angle: 90°, Beam Angle: 120° |
| Dimming Options                     | Non-Dimmable, TBC, DALI Dimmable  |
| Correlated Colour Temperature (CCT) | CCT: 3000K, CCT: 4000K, CCT: 5000K  |
| Accessories                         | Microwave Sensor, PIR Sensor, ZigBee Controls, DMX Controls                               |

## Product Options

| ATTRIBUTE       | VALUES  |
|-----------------|---|
| Beam Angle      | TBC, Beam Angle: 15°, Beam Angle: 30°, Beam Angle: 60°, Beam Angle: 90°, Beam Angle: 120° |
| Dimming Options | Non-Dimmable, TBC, DALI Dimmable  |
| Accessories     | Microwave Sensor, PIR Sensor, ZigBee Controls, DMX Controls                               |

## Certification and Compliance

