

## Jacka Series



### Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 430W, 432W, 434W, 436W, 438W, 440W, 442W, 444W, 446W, 448W, 450W
Efficacy	140lm/W, 160lm/W
Correlated Colour Index (CRI)	>70, >80, TBC
IP Rating	66, TBC
IK Rating	08
Voltage	AC100-277V, AC277-480V

ATTRIBUTE	VALUES
Mounting Options	Suspended, TBC, Bracket Mounted
Beam Angle	TBC, Beam Angle: 15°, Beam Angle: 30°, Beam Angle: 60°, Beam Angle: 90°, Beam Angle: 120°
Dimming Options	Non-Dimmable, TBC, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 5000K
Accessories	Microwave Sensor, PIR Sensor, ZigBee Controls, DMX Controls

## Product Options

ATTRIBUTE	VALUES
Beam Angle	TBC, Beam Angle: 15°, Beam Angle: 30°, Beam Angle: 60°, Beam Angle: 90°, Beam Angle: 120°
Dimming Options	Non-Dimmable, TBC, DALI Dimmable
Accessories	Microwave Sensor, PIR Sensor, ZigBee Controls, DMX Controls

## Certification and Compliance

