

## Tabbita Series - 1000



### Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 100W
Efficacy	120lm/W
Correlated Colour Index (CRI)	>80, >90, TBC
MacAdam Ellipse (SDCM)	<3
IP Rating	20, TBC
IK Rating	05
Voltage	AC220-240V, 50/60Hz
Light Source & Brand	LED: Lumileds 2835
Driver	Driver: BOKE, Driver: Eaglerise, Driver: SCPOWER
Size - Diameter	Diameter: 1000mmØ
Size - Height	Height: 100mmH
Weight	Weight: 15.7kg
Beam Angle	TBC, Beam Angle: 120°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Material of Optics- Glare control	Optics Material: Polycarbonate
Operating Temperature	Operating Temperature: -20°C to 35°C
Trim / Outer Colour	Trim/Outer: White, Trim/Outer: Black
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 6000K
Mounting Options	Suspended, TBC, Recessed, Ceiling Mounted
Lens Options	TBC, MicroPrismatic Diffuser, Opal Diffuser
Accessories	5m Suspension Kit, 2m Suspension Kit
Lamp Life	Lamp Life: L80 B10 @ 4K, CRI80

## Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 1000mmØ
Size - Height	Height: 100mmH
Beam Angle	TBC, Beam Angle: 120°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable

ATTRIBUTE	VALUES
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -20°C to 35°C
Accessories	5m Suspension Kit, 2m Suspension Kit

## Certification and Compliance

