

Bowen Series - 350

[AES-25-HB420-200]



Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 200W, 240W
Efficacy	150lm/W, 180lm/W
Correlated Colour Index (CRI)	>80, TBC
MacAdam Ellipse (SDCM)	<5
IP Rating	65, TBC
IK Rating	10
Voltage	AC100-277V
Light Source & Brand	LED: SMD
Driver	Driver: Phillips, Driver: Meanwell, Driver: SOSEN
Size - Diameter	Diameter: 350mmØ
Size - Height	Height: 155mmH
Mounting Options	TBC, Bracket Mounted, Ceiling Mounted, Hook Mounted, Loop Hanging
Beam Angle	TBC, Beam Angle: 60°, Beam Angle: 90°, Beam Angle: 120°
Dimming Options	Non-Dimmable, TBC, 1-10V Dimmable, DALI Dimmable

ATTRIBUTE	VALUES
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 6000K
Accessories	PIR Sensor, Daylight Sensor, ZigBee Controls
Lens Options	TBC, Ripple Lens
Weight	Weight: 5.6kg

Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 350mmØ
Size - Height	Height: 155mmH
Beam Angle	TBC, Beam Angle: 60°, Beam Angle: 90°, Beam Angle: 120°
Dimming Options	Non-Dimmable, TBC, 1-10V Dimmable, DALI Dimmable
Accessories	PIR Sensor, Daylight Sensor, ZigBee Controls

Certification and Compliance

