

# Bowen Series - 350



## Technical Specifications

| ATTRIBUTE                           | VALUES  |
|-------------------------------------|---|
| Wattages                            | TBC, 200W, 240W   |
| Efficacy                            | 150lm/W, 180lm/W  |
| Correlated Colour Index (CRI)       | >80, TBC  |
| MacAdam Ellipse (SDCM)              | <5  |
| IP Rating                           | 65, TBC   |
| IK Rating                           | 10  |
| Voltage                             | AC100-277V  |
| Light Source & Brand                | LED: SMD  |
| Driver                              | Driver: Phillips, Driver: Meanwell, Driver: SOSEN                 |
| Size - Diameter                     | Diameter: 350mmØ  |
| Size - Height                       | Height: 155mmH  |
| Mounting Options                    | TBC, Bracket Mounted, Ceiling Mounted, Hook Mounted, Loop Hanging |
| Beam Angle                          | TBC, Beam Angle: 60°, Beam Angle: 90°, Beam Angle: 120°           |
| Dimming Options                     | Non-Dimmable, TBC, 1-10V Dimmable, DALI Dimmable                  |
| Correlated Colour Temperature (CCT) | CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 6000K                    |

| ATTRIBUTE    | VALUES                                       |
|--------------|--|
| Accessories  | PIR Sensor, Daylight Sensor, ZigBee Controls |
| Lens Options | TBC, Ripple Lens                             |
| Weight       | Weight: 5.6kg                                |

## Product Options

| ATTRIBUTE       | VALUES  |
|-----------------|---|
| Size - Diameter | Diameter: 350mmØ  |
| Size - Height   | Height: 155mmH  |
| Beam Angle      | TBC, Beam Angle: 60°, Beam Angle: 90°, Beam Angle: 120° |
| Dimming Options | Non-Dimmable, TBC, 1-10V Dimmable, DALI Dimmable        |
| Accessories     | PIR Sensor, Daylight Sensor, ZigBee Controls            |

## Certification and Compliance

