

Fairfield Series



Technical Specifications

ATTRIBUTE	VALUES
Wattages	100W, 150W, 200W, 240W
Efficacy	160lm/W, 200lm/W
Correlated Colour Index (CRI)	CRI: >70, CRI: >80
IP Rating	IP65
IK Rating	IK08

ATTRIBUTE	VALUES
Voltage	AC100-277V
Light Source & Brand	LED: Lumileds SMD
Driver	Driver: SOSEN
Size - Diameter	Diameter: 273mmØ, Diameter: 300mmØ, Diameter: 330mmØ, Diameter: 355mmØ
Size - Height	Height: 156mmH, Height: 159mmH, Height: 162mmH, Height: 167mmH
Beam Angle	Beam Angle: 60°, Beam Angle: 90°, Beam Angle: 120°
Dimming Options	Non-Dimmable, 0-10V Dimmable, 1-10V Dimmable, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 5000K
Accessories	Microwave Sensor, PIR Sensor, CCT Selectable Switch, Power Selectable Switch, Casambi Wireless Controls, Zhaga Controls

Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 273mmØ, Diameter: 300mmØ, Diameter: 330mmØ, Diameter: 355mmØ
Size - Height	Height: 156mmH, Height: 159mmH, Height: 162mmH, Height: 167mmH
Beam Angle	Beam Angle: 60°, Beam Angle: 90°, Beam Angle: 120°
Dimming Options	Non-Dimmable, 0-10V Dimmable, 1-10V Dimmable, DALI Dimmable
Accessories	Microwave Sensor, PIR Sensor, CCT Selectable Switch, Power Selectable Switch, Casambi Wireless Controls, Zhaga Controls

Certification and Compliance

