Wacol Series

Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 100W, 120W, 150W, 200W
Efficacy	140lm/W
Correlated Colour Index (CRI)	>70, >80, TBC
IP Rating	65, TBC
IK Rating	08

ATTRIBUTE	VALUES
Voltage	AC100-277V
Mounting Options	TBC, Bracket Mounted, Ceiling Mounted, Hook Mounted, Loop Hanging
Beam Angle	TBC, Beam Angle: 40°, Beam Angle: 60°, Beam Angle: 85°, Beam Angle: 90°, Beam Angle: 120°, Beam Angle: 30° x 90°
Dimming Options	Non-Dimmable, TBC, 0-10V Dimmable, 1-10V Dimmable, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 5000K
Accessories	Microwave Sensor, PIR Sensor, Daylight Sensor, ZigBee Controls

Product Options

ATTRIBUTE	VALUES
Beam Angle	TBC, Beam Angle: 40°, Beam Angle: 60°, Beam Angle: 85°, Beam Angle: 90°, Beam Angle: 120°, Beam Angle: 30° x 90°
Dimming Options	Non-Dimmable, TBC, 0-10V Dimmable, 1-10V Dimmable, DALI Dimmable
Accessories	Microwave Sensor, PIR Sensor, Daylight Sensor, ZigBee Controls

Certification and Compliance

IP65   IK8

NOT DIMMABLE

40°   60°   85°   90°   120°