

Valkyrie Series - 50-80W

[AES-03-FL06-G7-50-80W]



Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 50W, 80W
Efficacy	140lm/W
Correlated Colour Index (CRI)	>80, TBC
MacAdam Ellipse (SDCM)	<6
IP Rating	65, TBC
IK Rating	08
Voltage	AC120-277V, 50/60Hz
Light Source & Brand	LED: Lumileds 2835
Driver	Driver: SOSEN
Size - Length	Length: 284mmL
Size - Width	Width: 236mmW
Size - Height	Height: 111mmH
Weight	Weight: 1.85kg
Vertical Rotation	Vertical Rotation: 210°
Beam Angle	TBC, Beam Angle: 15°, Beam Angle: 30°, Beam Angle: 60°, Beam Angle: 90°, Beam Angle: 150°, Beam Angle: 60° x 20°, Beam Angle: 156° x 71°
Dimming Options	Non-Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Die-Cast ADC12 Aluminum
Material of Optics-Glare control	Optic Material: Tempered Glass
Corrosion Resistance	Corrosion Resistance: C5
Operating Temperature	Operating Temperature: -40°C to+50°C
Trim / Outer Colour	Trim/Outer: White, Trim/Outer: Black, Trim/Outer: Grey
Reflector / Internal Colour	Reflector/Internal: White
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 5700K
Mounting Options	TBC, Wall Mounted
Lens Options	TBC, Polycarbonate
Accessories	PIR Sensor, Lens
Lamp Life	Lamp Life: L80 B10 @ 4K, CRI80

Product Options

ATTRIBUTE	VALUES
Size - Length	Length: 284mmL
Size - Height	Height: 111mmH
Beam Angle	TBC, Beam Angle: 15°, Beam Angle: 30°, Beam Angle: 60°, Beam Angle: 90°, Beam Angle: 150°, Beam Angle: 60° x 20°, Beam Angle: 156° x 71°
Dimming Options	Non-Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Die-Cast ADC12 Aluminum
Operating Temperature	Operating Temperature: -40°C to +50°C
Accessories	PIR Sensor, Lens

Certification and Compliance

