

Quanda Series - 200W

[AES-03-HBL02-G4-200W]



Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 152W, 154W, 156W, 158W, 160W, 162W, 164W, 166W, 168W, 170W, 172W, 174W, 176W, 178W, 180W, 182W, 184W, 186W, 188W, 190W, 192W, 194W, 196W, 198W, 200W
Efficacy	130lm/W
Correlated Colour Index (CRI)	>80, TBC
MacAdam Ellipse (SDCM)	<6
IP Rating	65, TBC
IK Rating	10
Voltage	AC120-277V, 50/60Hz
Light Source & Brand	LED: Lumileds 2835
Driver	Driver: SOSEN
Size - Diameter	Diameter: 380mmØ
Size - Height	Height: 200mmH
Weight	Weight: 5.5kg
Beam Angle	TBC, Beam Angle: 60°, Beam Angle: 90°, Beam Angle: 120°
Dimming Options	Non-Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Die Cast Aluminium
Material of Optics-Glare control	Optics Material: Polycarbonate
Corrosion Resistance	Corrosion Resistance: C5
Operating Temperature	Operating Temperature: -40°C to +50°C
Trim / Outer Colour	Trim/Outer: Black
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 5700K
Mounting Options	Suspended, TBC, Ceiling Mounted
Accessories	Microwave Sensor, IP65 Connectors, Mounting Brackets, Aluminium Reflector, PC Reflector, Chain
Lamp Life	Lamp Life: L80 B10 @ 4K, CRI80

Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 380mmØ
Size - Height	Height: 200mmH
Beam Angle	TBC, Beam Angle: 60°, Beam Angle: 90°, Beam Angle: 120°
Dimming Options	Non-Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Die Cast Aluminium
Operating Temperature	Operating Temperature: -40°C to+50°C
Accessories	Microwave Sensor, IP65 Connectors, Mounting Brackets, Aluminium Reflector, PC Reflector, Chain

Certification and Compliance

