

## Oakey Series - 200W



### Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 152W, 154W, 156W, 158W, 160W, 162W, 164W, 166W, 168W, 170W, 172W, 174W, 176W, 178W, 180W, 182W, 184W, 186W, 188W, 190W, 192W, 194W, 196W, 198W, 200W
Efficacy	140lm/W
Correlated Colour Index (CRI)	>80, TBC
MacAdam Ellipse (SDCM)	<6
IP Rating	65, TBC
IK Rating	10
Voltage	AC120-277V, 50/60Hz
Light Source & Brand	LED: Lumileds 2835
Driver	Driver: SOSEN
Size - Length	Length: 1066mmL
Size - Width	Width: 115mmW
Size - Height	Height: 111mmH
Weight	Weight: 3.65kg
Beam Angle	TBC, Beam Angle: 120°, Beam Angle: 90° x 120°, Beam Angle: 60° x 120°
Dimming Options	Non-Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Die Cast Aluminium
Material of Optics-Glare control	Optics Material: Polycarbonate
Corrosion Resistance	Corrosion Resistance: C5
Operating Temperature	Operating Temperature: -40°C to +50°C
Trim / Outer Colour	Trim/Outer: Black
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 5700K, CCT: 6500K
Mounting Options	Suspended, TBC, Ceiling Mounted
Accessories	Microwave Sensor, IP65 Connectors, Mounting Brackets
Lifetime	Reported L80 @ 85° >102,000 Hrs - As outlined within IESNA Standards, Projected Lifetime can be up to 6 x the reported lifetimes

## Product Options

ATTRIBUTE	VALUES
Size - Length	Length: 1066mmL
Size - Height	Height: 111mmH
Beam Angle	TBC, Beam Angle: 120°, Beam Angle: 90° x 120°, Beam Angle: 60° x 120°
Dimming Options	Non-Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Die Cast Aluminium
Operating Temperature	Operating Temperature: -40°C to+50°C
Accessories	Microwave Sensor, IP65 Connectors, Mounting Brackets

## Certification and Compliance

