

# Jennings Series - 800-1000W

[AES-03-FL07-G9-800-1000W]



## Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 800W, 1000W
Efficacy	150lm/W
Correlated Colour Index (CRI)	>70, TBC
MacAdam Ellipse (SDCM)	<6
IP Rating	66, TBC
IK Rating	10
Voltage	AC100-277V, 50/60Hz
Light Source & Brand	LED: SMD 5050
Driver	Driver: Inventronics
Size - Diameter	Diameter: 554mmØ
Size - Width	Width: 593mmW
Size - Height	Height: 467mmH
Weight	Weight: 28.7kg
Tilt	Tilt: 210°
Beam Angle	TBC, Beam Angle: 15°, Beam Angle: 30°, Beam Angle: 45°, Beam Angle: 80°
Dimming Options	Non-Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Material of Optics- Glare control	Optics Material: Polycarbonate
Corrosion Resistance	Corrosion Resistance: C5
Operating Temperature	Operating Temperature: -40°C to+50°C
Trim / Outer Colour	Trim/Outer: Black
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 5700K
Mounting Options	TBC, Slipfitter, U-Shape Bracket Mounted, Base Mounted
Accessories	20kV Surge Protection Device, Aiming Position Laser, Anti-glare Cover
Lifetime	Reported L80 @ 85° >102,000 Hrs - As outlined within IESNA Standards, Projected Lifetime can be up to 6 x the reported lifetimes

## Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 554mmØ
Size - Height	Height: 467mmH
Beam Angle	TBC, Beam Angle: 15°, Beam Angle: 30°, Beam Angle: 45°, Beam Angle: 80°
Dimming Options	Non-Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -40°C to+50°C
Accessories	20kV Surge Protection Device, Aiming Position Laser, Anti-glare Cover

## Certification and Compliance

