

Eagleby Series

[AES-01-HB01]



Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 50W, 70W, 90W, 100W, 120W, 150W, 200W, 240W, 300W
Efficacy	140lm/W
Correlated Colour Index (CRI)	>70, >80, TBC
IP Rating	65, TBC

ATTRIBUTE	VALUES
IK Rating	08, 10
Voltage	AC100-277V
Size - Diameter	Diameter: 264mmØ, Diameter: 383mmØ
Size - Height	Height: 122mmH, Height: 171mmH, Height: 182mmH, Height: 201mmH, Height: 210mmH, Height: 254mmH
Beam Angle	TBC, Beam Angle: 30°, Beam Angle: 50°, Beam Angle: 60°, Beam Angle: 65°, Beam Angle: 85°, Beam Angle: 90°, Beam Angle: 110°, Beam Angle: 113°, Beam Angle: 120°
Dimming Options	Non-Dimmable, TBC, 0-10V Dimmable, 1-10V Dimmable, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 5000K
Accessories	Microwave Sensor, PIR Sensor, Daylight Sensor, ZigBee Controls

Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 264mmØ, Diameter: 383mmØ
Size - Height	Height: 122mmH, Height: 171mmH, Height: 182mmH, Height: 201mmH, Height: 210mmH, Height: 254mmH
Beam Angle	TBC, Beam Angle: 30°, Beam Angle: 50°, Beam Angle: 60°, Beam Angle: 65°, Beam Angle: 85°, Beam Angle: 90°, Beam Angle: 110°, Beam Angle: 113°, Beam Angle: 120°
Dimming Options	Non-Dimmable, TBC, 0-10V Dimmable, 1-10V Dimmable, DALI Dimmable
Accessories	Microwave Sensor, PIR Sensor, Daylight Sensor, ZigBee Controls

Certification and Compliance

