

Kadina Series

[AES-01-HB08] Kadina Series

Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 100W, 120W, 150W, 200W, 240W, 300W
Efficacy	130lm/W, 140lm/W, 150lm/W, 160lm/W
Correlated Colour Index (CRI)	>70, >80, TBC
IP Rating	65, TBC
IK Rating	08, 10
Voltage	AC100-277V
Beam Angle	TBC, Beam Angle: 30°, Beam Angle: 50°, Beam Angle: 60°, Beam Angle: 90°, Beam Angle: 120°
Size - Diameter	Diameter: 360mmØ, Diameter: 388mmØ
Dimming Options	Non-Dimmable, TBC, 1-10V Dimmable, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 5000K
Accessories	Microwave Sensor, PIR Sensor, Daylight Sensor, Mounting Brackets, ZigBee Controls, Aluminium Reflector, PC Reflector, Reflector Cup

Product Options

ATTRIBUTE	VALUES
Beam Angle	TBC, Beam Angle: 30°, Beam Angle: 50°, Beam Angle: 60°, Beam Angle: 90°, Beam Angle: 120°
Size - Diameter	Diameter: 360mmØ, Diameter: 388mmØ
Dimming Options	Non-Dimmable, TBC, 1-10V Dimmable, DALI Dimmable
Accessories	Microwave Sensor, PIR Sensor, Daylight Sensor, Mounting Brackets, ZigBee Controls, Aluminium Reflector, PC Reflector, Reflector Cup

Certification and Compliance

